



flexiHaul™

Flexible Fronthaul and Backhaul Solution for 4G and Beyond

HSN-8100 PRODUCT OVERVIEW

HSN-8100 is a member of the cost-effective and highly scalable flexiHaul™ product line. At 1U in height, HSN-8100 is also compact and is generally deployed at a remote location near to RRHs or other any cell element in order to serve as a remote terminal for HSN-8500 or HSN-8300 aggregator. Like the other units in the flexiHaul product line, HSN-8100 has a flexible, pay-as-you-grow architecture with plug-in service cards, thereby allowing the customer the ability to choose any combination of supported services as well as facilitate easy operation and maintenance.

This unit includes two service slots used to transport service via CWDM/DWDM over dark fiber.

HSN-8100 supports point to point, ring and linear chain are supported with ring protection. In addition, HSN-8100 is efficiently managed by EMS, which provides the necessary tools for both traffic provisioning and overall system monitoring.

Primary Applications

- . CPRI/ OBSAI fronthaul interface in C-RAN architecture between BBU and RRHs
- . Ethernet backhaul interface for distributed RAN architecture
- . TDM backhaul interface for 2G BTS
- . G-PON backhaul for small cells such as Femto and WiFi
- . Wavelength switching, grooming and aggregation

Enabling the C-RAN fronthaul and small cell backhaul in a single box



[HSN-8100]

Key Features

- . CPRI (option 2, 3, 5, 7), OBSAI (3.072, 6.144 Gbps), GbE, G-PON, E1, STM-1
- . Multi-protocol support
- . Supports 1 or 2 rings
- . 4 x CPRI muxing into 10 Gbps line
- . CPRI delay (one-way) : transponder < 1 μ s, muxponder < 3 μ s
- . Jitter : less than ± 2 ppb
- . Ring protection less than 50 ms
- . FEC (Forward Error Correction) support
- . Topology : point to point, ring, linear chain

Architecture

- . High scalability (Max. 8 ports CPRI)
- . Plug-in architecture: any module in any slot

OAM and maintainability

- . Alarms, statistics, performance monitoring
- . Remote management via optical supervisor channel (OSC)
- . Local / remote logical loopbacks
- . Connectivity, signal level, delay, distance measurement

HSN-8100 SYSTEM SPECIFICATION

System Capacity

Service slots	2
CPRI capacity	Up to 8 channels
CWDM / DWDM	ITU-T G.694.1, ITU-T G.694.2
Transmission distance	Up to 20 km

Channel Interface

Service interface	CPRI (option 2, 3, 5, 7), OBSAI (3.072, 6.144 Gbps), GbE, G-PON, E1, STM-1
Optical connector type	LC / APC, LC / PC, SC / APC

Muxponder / Multi-rate transponder

Muxponder	4 ports CPRI (option 2, 3) / OBSAI (3.072 Gbps) 2 ports CPRI (option 5) / OBSAI (6.144 Gbps)
Multi-rate transponder	4 ports CPRI (option 3, 5, 7) / OBSAI (3.072, 6.144 Gbps)

Configurations / Power / Environmental

Point-to-Point	Hub and spoke configuration
Ring	Up to 2 rings
Power	- 42 to - 60 VDC
Environmental	Operating : - 20 °C to 60 °C Humidity : 10 % to 90 %

Protection / Switching

Switching time	< 50 ms
----------------	---------

OAM

Fault control	Alarm severity : critical, major, minor, warning
Classification level	Unit, module, port
Performance monitoring	15 min, past day
Line/ CPRI error monitoring	BIP, CV, ES, SES, UAS, Input / Output power of CPRI / OBSAI channels
Test function	Local / remote loopback Delay time
Ext. equipment control	12 ports open / closed external equipment warnings
Visual LED Indicators	System activity, system failure, ACO, alarms status (critical, major, minor)

Network Management

Operation	EMS (server, client), Craft Terminal Interface
Protocols	TL-1
Physical interface	10 / 100 / 1000Base-TX

Physical Characteristics

Dimension	19", 44.6 (H) x 483 (W) x 435 (D) mm
Power consumption	116 W (Fully loaded)

Supported service modules

OTU3F

Type	3 ports CPRI / OBSAI Transponder
Protocols	CPRI (option 3, 5), OBSAI (3.072, 6.144 Gbps)
Client / WDM ports	3/3
FEC support	non
CPRI dealy(one-way)	< 1 μ s

ATU3F

Type	3 ports CPRI / OBSAI Transponder
Protocols	CPRI (option 3, 5), OBSAI (3.072, 6.144 Gbps)
Client / WDM ports	3/3
FEC	support
CPRI dealy(one-way)	< 1 μ s (without FEC)

OTU4G

Type	4 ports CPRI or 3 ports CPRI + 1 port GbE Transponder
Protocols	CPRI (option 3, 5, 7), GbE
Client / WDM ports	4/4
FEC	support
CPRI dealy(one-way)	< 1 μ s (without FEC)

604TU

Type	Ethernet Transponder
Protocols	4 ports GbE
Client / WDM ports	4/4
FEC	non

OTU10G

Type	4 ports CPRI Muxponder
Protocols	Client side : CPRI (option 2, 3) WDM side : 10 Gbps
Client / WDM ports	4/1
FEC	non
CPRI delay (one-way)	< 3 μ s

ATU10G

Type	4 ports CPRI Muxponder or 2 ports CPRI + 2 ports GbE
Protocols	Client side : CPRI (option 2, 3, 5), GbE WDM side : 10 Gbps
Client / WDM ports	4/1
FEC	non
CPRI delay (one-way)	< 3 μ s